Warwick Range



KD200 Kidney Dish

Long Life Re-usable Polypropylene Kidney Dish for use in Sterile Services, Decontamination Units, Hospitals, and Clinics



The Warwick Range of polypropylene products from Warwick SASCo was originally designed to offer an alternative to stainless steel products traditionally used in Hospitals.

This Range is now widely used in Sterile Services and Decontamination Units, Operating Rooms and Clinics due to its low cost, effective product design, and repeat performance results in hospital autoclaves.

Easily recognised by its distinct blue colour, the Warwick Range includes bowls, gallipots, kidney dishes, instrument trays, instrument protection, instrument boxes, traceability tags, measuring jugs, scope and instrument soaking containers.



Warwick House, Heathcote Way, Warwick, CV34 6TE

T: 00 44 (0)1926 422427 www.sasco.co.uk

Product Benefits

- Graduated measuring scale
- Lightweight, strong and durable 50% lighter than stainless steel.
- Improved removal of blood residue compared to Stainless Steel.
- Can be sterilized by Autoclave, Ethylene Oxide or Hydrogen Plasma.
- Grip feature moulded below rim to improve holding.
- Smooth edges and surfaces eliminate paper rips during packing and sterilization.

Product Specification

- 300ml Kidney Dish graduated to 300ml
- 200mm, x 45mm
- Pack Size 150
- The following standards ae applicable:
 - ISO 9001:2008

Quality Management System

- ISO 13485:2003
 - Medical Devices Quality Management System
- ISO 17664:2004

Sterilization of Medical Devices - Guidelines for the processing of re-sterilizable medical devices

– BS5452

Specifications for Hospital Hollow-ware made of Plastics Material

- Manufactured from high quality polypropylene
- Autoclavable up to 135 ° C

Guide to Using Warwick Products from Warwick SASCo

Cleaning

- Product should be washed before first use.
- Warwick Products are designed for a lengthy service and guaranteed for 1000 washes and sterilizations. Scouring and abrasive cleaners will reduce the performance of products.
- Product should be processed complying with requirements of ISO 17664.

Storage

- This product has a shelf life of 36 months from date of manufacture providing the recommended storage conditions are adhered to.
- Product should be stored in its primary packaging, off the floor on a pallet or shelf, and in a clean dry ventilated room at a temperature of 4 °C - 25 °C.