

# DSSW1000 1 Litre Disinfection Box with Strainer and Hinged Lid

Non-Sterile Disinfection Set for containing Sterile and Non-Sterile Equipment during Disinfection



The Warwick Range of polypropylene products from Warwick SASCo was originally designed to offer an alternative to stainless steel products traditionally used in Hospitals.

This Range is now widely used in Sterile Services and Decontamination Units, Operating Rooms and Clinics due to its low cost, effective product design, and repeat performance results in hospital autoclaves.

Easily recognised by its distinct blue colour, the Warwick Range includes bowls, gallipots, kidney dishes, instrument trays, instrument protection, instrument boxes, traceability tags, measuring jugs, scope and instrument soaking containers.



Warwick House, Heathcote Way, Warwick, CV34 6TE T: 00 44 (0)1926 422427 www.sasco.co.uk

# **Product Benefits**

- Lightweight, strong and durable 50% lighter than stainless steel.
- Can be used to disinfect both sterile and non-sterile equipment.
- Intended for manual sterilization by liquid soaking. Can be sterilized using Autoclave.
- Strong and durable container resistant to most hospital cleaning/ disinfectant chemicals.
- Suitable for daily use.
- Tight fitting lid reduces vapour exposure.
- Strainer design for rapid immersion and drainage.

### **Product Specification**

- Set comprises 1 litre tank and strainer
- 260mm x 130mm x 65mm
- Pack Size 20
  - The following stanards are applicable

## – ISO 9001:2008

- Quality Management System
- ISO 13485:2003
- Medical Devices Quality Management System
- ISO 17664:2004
  Sterilization of Medical Devices Guidelines for the processing of re-sterilizable medical devices
- Manufactured from high quality polypropylene
- Autoclavable up to 135 °C

#### Guide to Using Warwick Products from Warwick SASCo

#### Cleaning

- Product should be washed before first use.
- Warwick products are designed for a lengthy service. Scouring and abrasive cleaners will reduce the performance of products.
  - Product should be processed complying with requirements of ISO 17664.

#### Storage

- This product has a shelf life of 36 months from date of manufacture providing the recommended storage conditions are adhered to.
  - Product should be stored in its primary packaging, off the floor on a pallet or shelf, and in a clean dry ventilated room at a temperature of 4 °C 25 °C.