Warwick Range



IBXN290 Instrument Box - storage box and lid

Long Life Re-usable Polypropylene Instrument Box for use in Sterile Services, Decontamination Units and Hospitals



The Warwick Range of polypropylene products from Warwick SASCo was originally designed to offer an alternative to stainless steel products traditionally used in Hospitals.

This Range is now widely used in Sterile Services and Decontamination Units, Operating Rooms and Clinics due to its low cost, effective product design, and repeat performance results in hospital autoclaves.

Easily recognised by its distinct blue colour, the Warwick Range includes bowls, gallipots, kidney dishes, instrument trays, instrument protection, instrument boxes, traceability tags, measuring jugs, scope and instrument



Product Benefits

- Strong and durable, with solid lid.
- Suitable for containing and storing both sterile and non-sterile instruments and may be used for transportation of instruments.
- Can be sterilized by Autoclave, Ethylene Oxide or Hydrogen Plasma.

Product Specification

- Blue Instrument Box with Solid Lid
- 300x224x140mm
- Pack Size 12
- The following standards are applicable:
 - ISO 9001:2008

Quality Management System

- ISO 13485:2003

Medical Devices - Quality Management System

ISO 17664:2004

Sterilization of Medical Devices - Guidelines for the processing of re-sterilizable medical devices

- Manufactured from high quality polypropylene
- Autoclavable up to 135 ° C

Guide to Using Warwick Products from Warwick SASCo

Cleaning

- Product should be washed before first use.
- Warwick Products are designed for a lengthy service and guaranteed for 1000 washes and sterilizations. Scouring and abrasive cleaners will reduce the performance of products.
- Product should be processed complying with requirements of ISO 17664.

Storage

- This product has a shelf life of 36 months from date of manufacture providing the recommended storage conditions are adhered to.
- Product should be stored in its primary packaging, off the floor on a pallet or shelf, and in a clean dry ventilated room at a temperature of 4 °C - 25 °C.