

## TR30 Attachment Ring - Stainless steel tag attachment ring

Long Life Re-usable Tray Tag Attachment Ring for use in Sterile Services and Decontamination Units



The Warwick Range of polypropylene products from Warwick SASCo was originally designed to offer an alternative to stainless steel products traditionally used in Hospitals.

This Range is now widely used in Sterile Services and Decontamination Units, Operating Rooms and Clinics due to its low cost, effective product design, and repeat performance results in hospital autoclaves.

Easily recognised by its distinct blue colour, the Warwick Range includes bowls, gallipots, kidney dishes, instrument trays, instrument protection, instrument boxes, traceability tags, measuring jugs, scope and instrument soaking containers.



### Product Benefits

- Stainless steel ring for use with Traceability Tags.
- Can be securely attached to sterile sets and instrument trays to track and trace through decontamination processing.
- Allows for clear and easy identification of sets during processing.
- Lightweight, strong and durable.
- Can be sterilized by Autoclave, Ethylene Oxide or Hydrogen Plasma.

### Product Specification

- Stainless Steel Attachment Ring for Traceability Tags
- 30mm
- Pack Size 100
- The following standards are applicable:
  - **ISO 9001:2008**  
Quality Management System
  - **ISO 13485:2003**  
Medical Devices - Quality Management System
  - **ISO 17664:2004**  
Sterilization of Medical Devices - Guidelines for the processing of re-sterilizable medical devices
- Manufactured from high quality stainless steel
- Autoclavable up to 135 ° C

### Guide to Using Warwick Products from Warwick SASCo

#### Cleaning

- Product should be washed before first use.
- Warwick Products are designed for a lengthy service and guaranteed for 1000 washes and sterilizations. Scouring and abrasive cleaners will reduce the performance of products.
- Product should be processed complying with requirements of ISO17664.

#### Storage

- This product has a shelf life of 36 months from date of manufacture providing the recommended storage conditions are adhered to.
- Product should be stored in its primary packaging, off the floor on a pallet or shelf, and in a clean dry ventilated room at a temperature of 4 °C - 25°C.