

DSSW2711 Disinfection Set - Soaking container, strainer and lid

Non-Sterile Disinfection Set for containing Sterile and Non-Sterile Equipment during Disinfection



The Warwick Range of polypropylene products from Warwick SASCo was originally designed to offer an alternative to stainless steel products traditionally used in Hospitals.

This Range is now widely used in Sterile Services and Decontamination Units, Operating Rooms and Clinics due to its low cost, effective product design, and repeat performance results in hospital autoclaves.

Easily recognised by its distinct blue colour, the Warwick Range includes bowls, gallipots, kidney dishes, instrument trays, instrument protection, instrument boxes, traceability tags, measuring jugs, scope and instrument soaking containers.



Product Benefits

- Lightweight, strong and durable - 50% lighter than stainless steel.
- Can be used to disinfect both sterile and non-sterile equipment.
- Intended for manual sterilization by liquid soaking. Can be sterilized using Autoclave.
- Tight fitting lid reduces vapour exposure.
- Strong and durable - container resistant to most hospital cleaning/disinfectant chemicals.
- DSSW(V)2711 also available - 3 litre disinfection set with a vented lid.

Product Specification

- Set comprises 3 litre tank, strainer and plain lid
- Also available with vented lid
- 257mm x 180mm x 128mm
- Pack Size 5
- The following standards are applicable:
 - **ISO 9001:2008**
Quality Management System
 - **ISO 13485:2003**
Medical Devices - Quality Management System
 - **ISO 17664:2004**
Sterilization of Medical Devices - Guidelines for the processing of re-sterilizable medical devices
- Manufactured from high quality polypropylene
- Autoclavable up to 135 °C

Guide to Using Warwick Products from Warwick SASCo

Cleaning

- Product should be washed before first use.
- Warwick products are designed for a lengthy service. Scouring and abrasive cleaners will reduce the performance of products.
- Product should be processed complying with requirements of ISO17664.

Storage

- This product has a shelf life of 36 months from date of manufacture providing the recommended storage conditions are adhered to.
- Product should be stored in its primary packaging, off the floor on a pallet or shelf, and in a clean dry ventilated room at a temperature of 4 °C - 25 °C.